


ACO Industrial

Floor Drainage

RO280 range



Product range

and Specification

RO280H NW100 range



Full Flow Floor Trap with the following features:

- Manufactured from Stainless Steel 304 to ensure acid corrosion and stain resistance
- A double water seal to ensure odor-free operation
- Smooth surfaces for easy cleaning, minimum dirt collection and high flow rates
- A large sludge box which contains coarse slurry
- Easy to dismantle
- The discharge pipe is fully accessible once the drain has been dismantled
- Top flange type: Round (for epoxy floors) or Square (for tiled floors)
- Optional perforated outlet cap
- Top cover plate type: Slots/ Holes or Circular Aperture – as required
 - Flow rate: 4.5l/sec
 - Load capacity : 1500 kg
 - Outlet position: Bottom Horizontal
 - Outlet pipe outside diameter: 104/110mm


NOTE: Floor finish to be specified

Typical applications:

General Food Processing, Beverage manufacturing etc.



SQUARE FLANGE FOR TILES FLOORS



ROUND FLANGE FOR EPOXY FLOORS

rofo™


A brand of the ACO Group

ACO

Product range

and Specification

RO280V NW100 range





Full Flow Floor Trap with the following features:

- Manufactured from Stainless Steel 304 to ensure acid corrosion and stain resistance
- A double water seal to ensure odor-free operation
- Smooth surfaces for easy cleaning, minimum dirt collection and high flow rates
- A large sludge box which contains coarse slurry
- Easy to dismantle
- The discharge pipe is fully accessible once the drain has been dismantled
- Top flange type: Round (for epoxy floors) or Square (for tiled floors)
- Optional Perforated outlet cap
- Top cover plate type: Slots/ Holes or Circular Aperture – as required
 - Flow rate: 4.5l/sec
 - Load capacity : 1500 kg
 - Outlet position: Bottom Vertical
 - Outlet pipe outside diameter: 104/110mm


NOTE: Floor finish to be specified

Typical applications:

General Food Processing, Beverage manufacturing etc.




SQUARE FLANGE FOR TILES FLOORS



ROUND FLANGE FOR EPOXY FLOORS





Product range

and Specification

RO280 SH NW100 range 1-4 side inlets



Full Flow Floor Trap with the following features:


- Manufactured from Stainless Steel 304 to ensure acid corrosion and stain resistance
- A double water seal to ensure odor-free operation
- Smooth surfaces for easy cleaning, minimum dirt collection and high flow rates
- A large sludge box which contains coarse slurry
- The discharge pipe is fully accessible once the drain has been dismantled
- Easy to dismantle
- Optional perforated outlet cap
- Top flange type: Round (for epoxy floors) or Square (for tiled floors)
- Top cover plate type: Slots/ Holes or Circular Aperture – as required
- Extension for side inlets: 1,2,3 or 4 inlets
 - Flow rate: 4.5l/sec
 - Load capacity : 1500 kg
 - Outlet position: Bottom Horizontal
 - Outlet pipe outside diameter: 104/110mm

NOTE: Floor finish to be specified

Typical applications:

Where there is a need to connect sinks directly to floor trap under the ground





Product range

and Specification

RO280 SV NW100 range 1-4 side inlets



Full Flow Floor Trap with the following features:

- Manufactured from Stainless Steel 304 to ensure acid corrosion and stain resistance
- A double water seal to ensure odor-free operation
- Smooth surfaces for easy cleaning, minimum dirt collection and high flow rates
- A large sludge box which contains coarse slurry
- The discharge pipe is fully accessible once the drain has been dismantled
- Easy to dismantle
- Optional perforated outlet cap
- Top flange type: Round (for epoxy floors) or Square (for tiled floors)
- Top cover plate type: Slots/ Holes or Circular Aperture – as required
- Extension for side inlets: 1,2,3 or 4 inlets
 - Flow rate: 4.5l/sec
 - Load capacity : 1500 kg
 - Outlet position: Bottom Vertical
 - Outlet pipe outside diameter: 104/110mm


NOTE: Floor finish to be specified

Typical applications:

Where there is a need to connect sinks directly to floor trap under the ground



SQUARE FLANGE FOR TILES FLOORS



ROUND FLANGE FOR EPOXY FLOORS



Product range

and Specification

RO280H NW100 Heavy Duty


Full Flow Floor Trap with the following features:

- Manufactured from Stainless Steel 304 to ensure acid corrosion and stain resistance
- A double water seal to ensure odor-free operation
- Smooth surfaces for easy cleaning, minimum dirt collection and high flow rates
- A large sludge box which contains coarse slurry
- Easy to dismantle
- The discharge pipe is fully accessible once the drain has been dismantled
- Top flange type: Round (for epoxy floors) or Square (for tiled floors)
- Optional Perforated outlet cap
- Top cover plate type: Holes
 - Flow rate: 4.5l/sec
 - Load capacity : 2500 kg
 - Outlet position: Bottom Horizontal
 - Outlet pipe outside diameter: 104/110mm




NOTE: Floor finish to be specified

Typical applications:


Wherever there is a need for higher load capacity, such as general food processing etc.




PERFORATED
OUTLET CAP
(OPTIONAL)




SQUARE FLANGE
FOR TILES FLOORS



ROUND FLANGE
FOR EPOXY FLOORS



PERFORATED
OUTLET CAP
(OPTIONAL)



Product range

and Specification

RO280V NW100 Heavy Duty



Full Flow Floor Trap with the following features:

- Manufactured from Stainless Steel 304 to ensure acid corrosion and stain resistance
- A double water seal to ensure odor-free operation
- Smooth surfaces for easy cleaning, minimum dirt collection and high flow rates
- A large sludge box which contains coarse slurry
- Easy to dismantle
- The discharge pipe is fully accessible once the drain has been dismantled
- Top flange type: Round (for epoxy floors) or Square (for tiled floors)
- Optional Perforated outlet cap
- Top cover plate type: Holes
 - Flow rate: 4.5l/sec
 - Load capacity : 2500 kg
 - Outlet position: Bottom Vertical
 - Outlet pipe outside diameter: 104/110mm


NOTE: Floor finish to be specified

Typical applications:

Wherever there is a need for higher load capacity, such as general food processing etc.



SQUARE FLANGE
FOR TILES FLOORS



ROUND FLANGE
FOR EPOXY FLOORS

Product range

and Specification

RO280H NW100 Heavy Duty with Grating




Full Flow Floor Trap with the following features:

- Manufactured from Stainless Steel 304 to ensure acid corrosion and stain resistance
- A double water seal to ensure odor-free operation
- Smooth surfaces for easy cleaning, minimum dirt collection and high flow rates
- A large sludge box which contains coarse slurry
- Easy to dismantle
- The discharge pipe is fully accessible once the drain has been dismantled
- Top flange type: Square (for tiled floors)
- Optional Perforated outlet cap
- Grating frame type: Square
- Top cover plate type: Slots/ Holes or Circular Aperture – as required
 - Flow rate: 4.5l/sec
 - Load capacity : 2500 kg
 - Outlet position: Bottom Horizontal
 - Outlet pipe outside diameter: 104/110mm

NOTE: Floor finish to be specified

Typical applications:

Wherever there is a need for higher load capacity, such as packaging facilities etc.



SQUARE FLANGE FOR TILES FLOORS

Product range

and Specification

RO280V NW100 Heavy Duty with Grating




Full Flow Floor Trap with the following features:

- Manufactured from Stainless Steel 304 to ensure acid corrosion and stain resistance
- A double water seal to ensure odor-free operation
- Smooth surfaces for easy cleaning, minimum dirt collection and high flow rates
- A large sludge box which contains coarse slurry
- Easy to dismantle
- The discharge pipe is fully accessible once the drain has been dismantled
- Top flange type: Square (for tiled floors)
- Optional Perforated outlet cap
- Grating frame type: Square
- Top cover plate type: Slots/ Holes or Circular Aperture – as required
 - Flow rate: 4.5l/sec
 - Load capacity : 2500 kg
 - Outlet position: Bottom Vertical
 - Outlet pipe outside diameter: 104/110mm

NOTE: Floor finish to be specified

Typical applications:

Wherever there is a need for higher load capacity, such as packaging facilities etc.



SQUARE FLANGE FOR TILES FLOORS

Product range

and Specification

RO280H NW100 for Refuse Area




Full Flow Floor Trap with the following features:

- Manufactured from Stainless Steel 304 to ensure acid corrosion and stain resistance
- A double water seal to ensure odor-free operation
- Smooth surfaces for easy cleaning, minimum dirt collection and high flow rates
- A large sludge box which contains coarse slurry
- Easy to dismantle
- The discharge pipe is fully accessible once the drain has been dismantled
- Removable S/S sieve tray
- Top flange type: Square (for tiled floors)
- Optional Perforated outlet cap
- Grating frame type: Square
- Top cover plate type: Slots/ Holes or Circular Aperture – as required
 - Flow rate: 4.5l/sec
 - Load capacity : 2500 kg
 - Outlet position: Bottom Horizontal
 - Outlet pipe outside diameter: 104/110mm

NOTE: Floor finish to be specified

Typical applications:

Refuse areas in general food processing, Wine, Beverage, Dairy etc.



SQUARE FLANGE FOR TILES FLOORS

Product range

and Specification

RO280V NW100 for Refuse Area




Full Flow Floor Trap with the following features:

- Manufactured from Stainless Steel 304 to ensure acid corrosion and stain resistance
- A double water seal to ensure odor-free operation
- Smooth surfaces for easy cleaning, minimum dirt collection and high flow rates
- A large sludge box which contains coarse slurry
- Easy to dismantle
- The discharge pipe is fully accessible once the drain has been dismantled
- Removable S/S sieve tray
- Top flange type: Square (for tiled floors)
- Optional Perforated outlet cap
- Grating frame type: Square
- Top cover plate type: Slots/ Holes or Circular Aperture – as required
 - Flow rate: 4.5l/sec
 - Load capacity : 2500 kg
 - Outlet position: Bottom Vertical
 - Outlet pipe outside diameter: 104/110mm

NOTE: Floor finish to be specified

Typical applications:

Refuse areas in general food processing, Wine, Beverage, Dairy etc.



SQUARE FLANGE FOR TILES FLOORS

Your local sales contact

ACO Systems SA
122 Shad Road
Wadeville Ext 2
Germiston
Gauteng
South Africa
0157

Tel: +27 11 824 3525/6
Email: info@aco.co.za

ACO Systems Western / Northern Cape
Contact: Jean de Villiers
Email: jdevilliers@aco.co.za
Tel: +27 84 351 3525

ACO Systems KZN / Eastern Cape
Contact: Antonio Ravell
Email: aravell@aco.co.za
Tel: +27 83 273 6299

ACO Systems SADC
Contact: Rui de Almeida
Email: rdealmeida@aco.co.za
Tel: +27 64 754 7890

www.aco.co.za
www.buildingdrainage.aco
www.hygienefirst.com

Every product from ACO supports the ACO system chain

- Drainage channels and gratings
- Road and point drainage
- Access covers
- Manhole covers
- Oil separators
- Grease separators
- Bridge drains
- Parking area drainage
- Sport facility drainage

